

**What is claimed is:**

1. A packaging machine comprising:  
a cylindrical chute;  
5 means for bending an elongated bag-making film into a tubular form around said chute by mutually overlapping side edges of said film;  
a heater unit for longitudinally sealing said mutually overlapping side edges of said film;  
heater driving means for moving said heater unit between a sealing  
10 position at which said heater unit contacts said film and a retracted position at which said heater unit is separated from said chute; and  
an air cylinder for controlling compressive force with which said heater unit at said sealing position compresses said film against said chute by having air of a specified pressure supplied thereto.

Sub B112. The packaging machine of claim 1 further comprising pressure regulating means for regulating air pressure supplied to said air cylinder to a specified pressure level and a controller for controllably varying said specified pressure level.

3. The packaging machine of claim 1 wherein said heater driving means includes another air cylinder.
4. The packaging machine of claim 1 further comprising a support unit which supports said heater unit and is slidable towards and away from said chute, said heater driving means operating to move said heater unit between said sealing position and said retracted position by moving said support unit, said air cylinder acting only on said heater unit to control said compressive force.

5. The packaging machine of claim 4 further comprising support unit moving means for moving said support unit between a work area which includes both said sealing position and said retracted position and a non-working area which is farther away from said chute than said work area.

6. A packaging machine comprising:  
 a cylindrical chute;  
 means for bending an elongated bag-making film into a tubular form around said chute by mutually overlapping side edges of said film;  
 5 a heater unit for longitudinally sealing said mutually overlapping side edges of said film;  
 an air cylinder both for moving said heater unit between a sealing position at which said heater unit contacts said film and a retracted position at which said heater unit is separated from said chute and for controlling compressive force  
 10 with which said heater unit at said sealing position compresses said film against said chute;  
 air-pressure generating means for generating from a single air source having an initial air pressure both a higher air pressure for moving said heater unit and a lower air pressure, lower than said higher air pressure, for controlling said  
 15 compressive force; and  
 switching means for supplying to said air cylinder selectively either said higher pressure to thereby move said heater unit with respect to said film or said lower pressure to thereby control said compressive force.

7. The packaging machine of claim 6 further comprising control means for serving to additionally supply said higher pressure to said air cylinder for a specified length of time while said lower pressure is being supplied to said air cylinder by said switching means.

5

claim 8 wherein said

5

g mea

12. The packaging machine of claim 6 further comprising means for controllably varying said lower pressure while said lower pressure is being supplied to said air cylinder.

14. The packaging machine of claim 8 further comprising means for controllably varying said lower pressure while said lower pressure is being supplied to said air cylinder.

16. The packaging machine of claim 10 further comprising means for controllably varying said lower pressure while said lower pressure is being supplied to said air cylinder.

add B2